


Central Article Code: G65080C01-B

Created: 07/11/2019

Local Code: EB858

Modified: 21/11/2019



Final Outlook	G6501-B
Approval date	15/11/2019

PERFORMANCES

Voltage (V):	12 V
C20 (Ah):	85.0 20 h
Cranking (A):	800 EN
Charge:	WET
Technology:	Vented/Flooded
Grid:	Ca/Ca
Vibration:	V1 (30Hz+/-2Hz/3g/2h)
Endurance:	E1 (180 cycles@25%)

STD. DIMENSIONS

Length (mm ± 2):	306
Width (mm ± 2):	192
Height (mm ± 2):	192
Total Weight (kg ± 5%):	19.50

CONTAINER

Type:	G65	BLACK
Hold Down:	B1	
H.D. Adapter:	No	

COVER

Type:	Flat/Press	BLACK
Polarity:	ETN 1	
Terminals:	EN taper post	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Central	
Filter:	2 Filters	
Lateral Plug:	No	

PLUGS

Type:	1 x Vent Sealed	BLACK
-------	-----------------	-------

HANDLES

Type:	None
-------	------

OTHERS

Degassing Tube:	No
-----------------	----

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.