


Central Article Code: G31100C10-A


Created: 12/06/2012

Local Code: EG110B

Modified: 27/01/2017



Final Outlook	G3110-A
Approval date	01/07/2016



PERFORMANCES

Voltage (V):	12 V
C20 (Ah):	110.0 20 h
Cranking (A):	1000 SAE 7.2 v 30 Sec.
Charge:	WET
Technology:	Vented/Flooded
Grid:	Ca/Ca
Vibration:	V2 (30Hz+/-2Hz/6g/2h)
Endurance:	E2 (90 cycles@50%)

STD. DIMENSIONS

Length (mm ± 2):	330
Width (mm ± 2):	173
Height (mm ± 2):	240
Total Weight (kg ± 5%):	27.40

CONTAINER

Type:	G31 BLACK
Hold Down:	B0
H.D. Adapter:	No

COVER

Type:	Flat/Press integ BLACK
Polarity:	ETN 9
Terminals:	SAE A taper post
Terminal Adapter:	No
SOCI:	No
Ventilation:	Central
Filter:	No
Lateral Plug:	No

PLUGS

Type:	2 x Vent BLACK
-------	----------------

HANDLES

Type:	1 x Rigid BLACK
-------	-----------------

OTHERS

Degassing Tube:	No
-----------------	----

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.