


Central Article Code: D02046G12-A

Local Code: ES950

Created: 05/09/2005

Modified: 20/07/2023



Final Outlook	D0212-A
Approval date	01/10/2005

PERFORMANCES

Voltage (V):	12 V
C20 (Ah):	85.0 20 h
Cranking (A):	0 EN
Charge:	CHARGED
Technology:	GEL
Grid:	Ca/Ca
Vibration:	V3 (30Hz+/-2Hz/6g/20h)
Endurance:	300 cycles@100%

STD. DIMENSIONS

Length (mm ± 2):	349
Width (mm ± 2):	175
Height (mm ± 2):	235
Total Weight (kg ± 5%):	28.20

CONTAINER

Type:	D02	BLACK
Hold Down:	B0	
H.D. Adapter:	No	

COVER

Type:	Flat/Screw	BLACK
Polarity:	ETN 1	
Terminals:	EN taper post	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Independent	
Filter:	No	
Lateral Plug:	No	

PLUGS

Type:	6 x M18 Valve	GREY MEDIUM
-------	---------------	-------------

HANDLES

Type:	2 x Rigid	BLACK
-------	-----------	-------

OTHERS

Degassing Tube:	No
-----------------	----

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

DNV-GL type approved 2015/Used for Bosch